

FIG. 2




FIG. 3

4/14




FIG. 4A

FIG. 4B

Title: IMAGE-PROCESSING DEVICE, IMAGE-PROCESSING METHOD AND SOLID-STATE IMAGE-PICKUP DEVICE

5/14

States of sensor bias	sensor k	oias							
	state	accumulation	RESS	LOADS	PR	CL	RESN	LOADN	
GATE	selected	VCCSGHI	Lo	VCCSGHR	VCCSGHR	VCCSGHR+ VCCSDBX 2	Lo1	VCCSGHR	
	non selected		Lo	Lo	ា	Lo	ما	Lo	, ;
SOURCE selected	selected	turning "on" (VCCSD1)	VMPR	VCCSGHR-VthS	VCCVPS	VCCSDBX 2	VMPR	VCCSGHR-VthN	5/14
DRAIN	selected	VCCSDI	HIZ	VCCSDR	turning "on" (VCCVPS)	turning "on" (VCCSDB X 2)	HiZ	VCCSDR	
	non selected		HiZ	VCCSDR	VCCVPS	VCCSDR	HiZ	VCCSDR	

FIG 5

6/14






FIG. 6

7/14



8/14



9/14






FIG. 9


10/14




11/14



12/14



13/14



14/14

